

AC FAN

JAMICON®

120X120X38 mm

KA1238-0 Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : ±10%
- **Impedance protected**

SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
KA1238H1B0	Dual Ball	100 - 125	50/60	82/96	0.272/0.311	2600/3000	0.30	23/20	42/46	538
KA1238M1B0			50/60	75/85	0.211/0.268	2400/2700	0.25	15/14	39/43	
KA1238L1B0A			50/60	78/77	0.216/0.134	2450/2450	0.20	12/12	38/38	
KA1238L1B0B			50/60	64/43	0.129/0.057	2100/1500	0.20	9/8	34/29	
KA1238L1B0C			50/60	75/64	0.211/0.129	2400/2100	0.20	11/11	39/34	
KA1238H1S0	Sleeve		50/60	82/96	0.272/0.311	2600/3000	0.30	23/20	42/46	
KA1238M1S0			50/60	75/85	0.211/0.268	2400/2700	0.25	15/14	39/43	
KA1238L1S0A			50/60	78/77	0.216/0.134	2450/2450	0.20	12/12	38/38	
KA1238L1S0B			50/60	64/43	0.129/0.057	2100/1500	0.20	9/8	34/29	
KA1238L1S0C			50/60	75/64	0.211/0.129	2400/2100	0.20	11/11	39/34	
KA1238H2B0	Dual Ball	220 - 240	50/60	82/96	0.272/0.311	2600/3000	0.20	23/20	42/46	
KA1238M2B0			50/60	75/85	0.211/0.268	2400/2700	0.16	15/14	39/43	
KA1238L2B0A			50/60	76/78	0.207/0.129	2450/2450	0.10	13/13	38/38	
KA1238L2B0B			50/60	64/43	0.129/0.057	2100/1500	0.10	9/8	34/29	
KA1238L2B0C			50/60	75/64	0.211/0.129	2400/2100	0.10	13/11	35/28	
KA1238H2S0	Sleeve		50/60	82/96	0.272/0.311	2600/3000	0.20	23/20	42/46	
KA1238M2S0			50/60	75/85	0.211/0.268	2400/2700	0.16	15/14	39/43	
KA1238L2S0A			50/60	76/78	0.207/0.129	2450/2450	0.10	13/13	38/38	
KA1238L2S0B			50/60	64/43	0.129/0.057	2100/1500	0.10	9/8	34/29	
KA1238L2S0C			50/60	75/64	0.211/0.129	2400/2100	0.10	13/11	35/28	

Specifications subject to change without notice

