

FOWX2.E47474 - Fixed Capacitors for Use in Electronic Equipment - Component

Fixed Capacitors for Use in Electronic Equipment - Component

See General Information for Fixed Capacitors for Use in Electronic Equipment - Component

OKAYA ELECTRIC INDUSTRIES CO LTD

HEAD OFFICE. 16-9 TODOROKI

6 CHOME

SETAGAYA-KU, TOKYO 158-8543 JAPAN

E47474

Fixed Capacitors

Type Dsg	Capacitor Class	Voltage Rating (V)	Capacitance (μF) (Tolerance)	Resistance for RC Devices (ohms)	Lower Temp (°C)	Upper Temp (°C)
XF Series	X2	300 ac	0.01-1 μF (@)	—	-55	+110
LE Series	X2	310 ac	0.047-2.2 μF (##)	—	-55	+110
LE Series	X2	250~275 ac(*)	0.01-3.3 μF (##)	—	-55	+100
LE Series	X2	250~300 ac(*)	1.5-10 μF (##)	—	-55	+100
LE Series	X2	250~300 ac(*)	0.1-1 μF (##)	—	-55	+100/+110
LE Series	X2	250~310 ac(*)	0.1-2.2 μF (##)	—	-55	+100/+110
PA Series	X2	275 ac	0.01-2.2 μF (##)	—	-40	+100
PAB Series	X2	275 ac	0.01-0.22 μF (##)	—	-40	+100
RE Series	X2	275 ac	0.01-2.2 μF (##)	—	-55	+100
TA Series	X2	250 ac	0.033 μF (@)	120	-40	+85
XF Series	X2	300 ac	0.01-1 μF (@)	—	-55	+110
YF Series	Y2	300 ac	0.01-0.47 μF (#)	—	-55	+110
VEA Series	X2	300 ac	1.0-10.0 μF (#)	—	-40	+100
RMTE Series	X2	250 ac	0.22 μF (@)	120	-40	+100
3RMES Series	X2	250 ac	0.33 μF (@)&)	120	-40	+100
CRH Series	X2	500 ac	0.1~0.47 μF (@)	27, 33, 47, 68	-40	+85
3CRH Series	X2	500 ac	0.33~0.47 μF (@)&)	27, 33	-40	+85

CRE Series	X2	250 ac	0.1~0.5 μF (@)	50, 68, 150, 200	-40	+85
3CRE Series	X2	250 ac	0.3~0.5 μF (@)(&)	50, 68	-40	+85
6CRE Series	X2	250 ac	0.5 μF (@)(&&)	50	-40	+85
SK	X2	250ac	0.33-0.47 uF(@)	47-120	-40	+110
XEB22001-HT	X2	250ac	0.01uF(@)	220	-40	+100
XH/XHB	X2	500ac	0.01-0.47uF(@)	—	-40	+100
XYH753222-AN	X2/Y2	X2:500ac Y2:250ac	X2:0.075uF Y2:2200pF(@)	—	-40	+100
AU Series	X2	250 ac	0.033-0.1 μF (@)	10,47,or 120	-40	+100
YE Series	Y2	250 ac	0.001-0.1 μF (@)	—	-40	+100
XYE Series	X2/Y2	275 ac	X2:0.047-0.47μF (@) Y2:2*1000-2*4700pF (@)	—	-40	+85
RE/REB Series	X2	275 ac	0.01-0.5 μF (@)	10,47,or 120	-40	+100
RPEL121204 Series	X2	250 ac	0.2 μF (@)	120	-40	+100
XAB1201 Series	X2	125 ac	0.1 μF (@)	120	-40	+85
XA120033	X2	125 ac	0.033 μF (@)	120	-40	+85
XA1201	X2	125 ac	0.1 μF (@)	120	-40	+85
XE Series	X1/Y2	X1:275ac Y2:250ac	X1:0.001-1.0 μF (@) Y2:0.001-0.0068 μF (@)	—	-40	+100
XEB Series	X2/Y2	X2:250ac Y2:250ac	X2:0.001-1.0 μF (@) Y2:0.001-0.0068 μF (@)	—	-40	+85
XE Series	X2	X2:250ac	X2:0.01-1.0 μF (@)	10,47,120, 220 or 470	-40	+100
XEB Series	X2	X2:250ac	X2:0.01-1.0 μF (@)	10,47,120, 220 or 470	-40	+100
CRZ Series	X2	X2:250ac	X2:0.1, 0.2 μF (@)	120 or 220	-40	+100
3CRZ Series	X2	X2:250ac	X2:0.3, 0.5 μF (@)(&)	50	-40	+100
RE1201	X2	275 ac	0.1 μF (@)	120	-40	+100
SK10A2E-12033	X2	250 ac	0.33μF (@)(&&)	120	-40	+100

Investigated to ANSI/UL 60384-14 (2nd ed.)

Type Dsg	Capacitor Class	Voltage Rating (V)	Capacitance (Tolerance)	Resistance for RC Devices (ohms)	Lower Temp (°C)	Upper Temp (°C)	Add'l Humidity Robustness Grades
----------	-----------------	--------------------	-------------------------	----------------------------------	-----------------	-----------------	----------------------------------

Fixed capacitor							
LE-MX-MR	X2	250~310 ac(*)	0.1~2.2 uF (##)	—	-55	+100/+110	IIIB

Note @: the model code may be followed by M for +/-20%.


#: the model code may be followed by K for +/-10%.

##: the model code may be followed by K for +/-10% or M for +/-20%.

& The model is constructed with 3 RC units in delta conjunction. The capacitance and resistance indicated are ratings for each single RC unit.

&& The model is constructed with 3 individual RC units in one case. The capacitance and resistance indicated are ratings for each single RC unit.

*****: One or more voltage rating cover in the voltage range may be provided.

Marking: Company name or trademarks "OKAYA" or  and type designation.

Last Updated on 2020-08-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"