


Metallized Polypropylene X2 Film Capacitor

Primary characteristics								
Parameter	Value	Unit						
Capacitance	10	nF						
Rated voltage	310	VAC						

Features

- Pb-free and **RoHS** compliant
- Plastic case according to UL94V-0
- Good self-healing effect



Part numbering system												
AFC	X2	103		К 1		04P		25	L	В		
Series code	Type: X2	Capacitance 10pF x 10 ³ = 10nF		pacitane blerance	vo	ated Itage arking	Lead width		Lead length	Lead configuration	Packing	
			J	±5%	1	310V	01P	2.5mm	25mm	See: lead configuration below	В	Bulk
			К	±10%			02P	5.0mm			Т	Таре
			М	±20%			03P	7.5mm				
					-		nP	n x 2.5mm				

Lead configuration																
Lead type	П	(je)-	ţ	П	8	R	Я	8	Ŗ	8	Ŗ				U U	ש ט ש
Code	L	М	Ν	В	С	D	Е	F	G	н	к	т	U	w	R	S



Specifications									
Parameter		Value	Unit						
Operating temperature range		-40 ~ 110	°C						
Climatic category		40/110/56/B							
Standard capacitance (C _R)		10	nF						
Capacitance tolerance		±10	%						
Rated voltage		310	VAC						
Insulation resistance	≤0.33µF	≥15000	MO						
@60±5 sec.; @100VDC	>0.33 μF	≥5000	MΩ						

Ordering information									
Part Number	Package	Shipping Quantity	Box dimensions						
AFCX2 103K104P25LB	13 x 11 x 5.0mm	500 pcs/polybag							

Disclaimer

Akyga passive reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Akyga passive or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on Akyga passive data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Akyga passive does not assume any liability arising out of the application or use of any product or circuit. Akyga passive products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Akyga passive. Customers using or selling Akyga passive components for use in such applications do so at their own risk and shall agree to fully indemnify Akyga passive and its subsidiaries harmless against all claims, damages and expenditures.