


## Metalized Polypropylene X2 Film Capacitor

















Primary characteristics		
Parameter	Value	Unit
Capacitance	22	nF
Rated voltage	310	VAC

### Features

- Pb-free and RoHS compliant
- Plastic case according to UL94V-0
- Good self-healing effect

Case dimensions						
						
Unit	W	H	T	P	$\phi d$	L
mm	13 $\pm 1.0$	11 $\pm 1.0$	5.0 $\pm 1.0$	10 $\pm 1.0$	0.8 $\pm 0.05$	25 MIN

Part numbering system													
AFC	X2	223	K		1	04P		25	L		B		
Series code	Type: X2	Capacitance $22\text{pF} \times 10^3 = 22\text{nF}$	Capacitance tolerance		Rated voltage marking	Lead width		Lead length	Lead configuration		Packing		
			J	$\pm 5\%$	1	310V	01P	2.5mm	-	See: <a href="#">lead configuration</a> below		B	Bulk
			K	$\pm 10\%$			02P	5.0mm				T	Tape
			M	$\pm 20\%$			03P	7.5mm					
							nP	$n \times 2.5\text{mm}$					

Lead configuration																
Lead type																
Code	L	M	N	B	C	D	E	F	G	H	K	T	U	W	R	S

Specifications			
Parameter	Value		Unit
Operating temperature range	-40 ~ 110		°C
Climatic category	40/110/56/B		
Standard capacitance (C <sub>R</sub> )	22		nF
Capacitance tolerance	±10		%
Rated voltage	310		VAC
Insulation resistance @60±5 sec.; @100VDC	≤0.33μF	≥15000	MΩ
	>0.33 μF	≥5000	

Ordering information			
Part Number	Package	Shipping Quantity	Box dimensions
AFCX2 223K104P25LB	13 x 11 x 5.0mm	500 pcs/polybag	---

## Disclaimer

Akyga passive reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Akyga passive or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on Akyga passive data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Akyga passive does not assume any liability arising out of the application or use of any product or circuit. Akyga passive products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Akyga passive. Customers using or selling Akyga passive components for use in such applications do so at their own risk and shall agree to fully indemnify Akyga passive and its subsidiaries harmless against all claims, damages and expenditures.