

HY ELECTRONIC (CAYMAN) LIMITED

www.hygroup.com.tw

Low VF=0.53V at IF=7.5A

## SCHOTTKY BARRIER RECTIFIERS

# REVERSE VOLTAGE 100 Volts FORWARD CURRENT 15 Amperes

#### **FEATURES**

- ●Very low profile typical hight of 1.1mm
- Ideal for automated placement
- Trench Schottky Technology
- High current capability, low VF
- High efficiency operation
- ●Fcompliant to RoHS Directive 2002/95/EC and accordance to WEEE 2002/96/EC
- For use in low voltage, high frequency inverters, free wheeling, switching power supplies, DC-DC converter, and polarity protection applications


#### **MECHANICAL DATA**

●Case: TO-277A (SMPC)

Molding compound meets UL 94 V-0 flammability rating

Terminals: Matte tin plated leads, solderable per

J-STD-002 and JESD 22-B102



### **MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Rating at 25℃ ambient temperature unless otherwise specified.

Single phase, half wave ,60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

MAXIMUM RATING	SS (T <sub>A</sub> = 25	o °C unless otherwise noted)		
CHARACTERISTICS	SYMBOL	HTS15L100		UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	100		V
Maximum RMS Voltage	VRMS	70		V
Maximum DC Blocking Voltage	VDC	100		V
Maximum Average Forward Rectified Current (See Fig.1)	I(AV)	15		Α
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load	IFSM	100		А
Peak repetitive reverse current at tp = 2 µs, 1 kHz	I <sub>RRM</sub>	1		Α
Operating Temperature Range	TJ	-55 to +150		$^{\circ}$ C
Storage Temperature Range	Тѕтс	-55 to +175		$^{\circ}$ C
ELECTRICAL CHARACTI	RISTICS (	T <sub>A</sub> = 25 °C unless otherwise n	oted)	
PARAMETER / CONDITIONS	SYMBOL	Тур	Max	UNIT
Breakdown voltage per diode	$V_{BR}$	105 (minimun)	-	٧
Forward Voltage (Note1)	V <sub>F</sub>	0.57 0.53 0.72 0.65	0.62 0.57 0.82 0.70	V
Maximum DC Reverse Current @TJ=25°C at Rated DC Bolcking Voltage @TJ=125°C	lr	160 40		uA mA
Typical Junction Capacitance (Note2)	CJ	621		pF
THERMAL CHARACTER	RISTICS (T	A = 25 °C unless otherwise not	ed)	
PARAMETER	SYMBOL	Typ HTS15L100		UNIT
Thermal Resistance Per Diode (Note3)	RθJL	4.0		°C/W

NOTES:1.300us pulse width,2% duty cycle.

2.Measured at 1.0 MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance junction to case.

Rev.1, 25-Apr-2017






Figure 1. Forward Current Derating Curve





Figure 2. Maximum NON-Repetitive



Instantaneous Forward Voltage (V) Figure 3. Typical Instantaneous Forward Characteristics Per Leg





Figure 4. Typical Reverse Characteristics



10 8 8 d=0.3 6 d=0.2 d=0.1 2 d=0.5 d=0.8 d=0.8 d=0.8 d=0.8 d=0.8

Figure 6. Forward Power Loss Characteristics

www.hygroup.com.tw

# **Legal Disclaimer Notice**



#### Disclaimer

ALL specifications and data are subject to be changed without notice to improve reliability function or design or other reasons.

HY makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the cotinuing production of any product. To the maximum extent permitted by applicable law, HY disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special,consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on HY's knowledge of typical requirements that are often placed on HY products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify HY's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, HY products are not designed for use in medical, life-saving, or life-sustaining applications or for any other applications in which the failure of the HY product could result in personal injury or death. Customers using or selling HY products not expressly indicated for use in such applications do so at their own risk. Please contact authorized HY personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of HY. Product names and markings noted herein may be trademarks of their respective owners.