

**JAMICON**

編號

CUSTOMER :ROPLA

NO: BFX1010015-1

**承 認 書**  
**APPROVE SHEET**

品 名:鋁 質 電 解 電 容 器  
PARTS : ALUMINUM ELECTROLYTIC CAPACITOR

USER NO.

CODE NO.

-----

TLR102M1EG21RT9

**承認欄(SIGNATURE)**  
簽認后,請簽回一份  
PLEASE RETURN US ONE COPY YOUR SIGNED SPECIFICATION  
AFTER YOU APPROVED OF IT.

	確認 CHECKER	作成 DESIGNER
	副 理 JAN.13.10 王 勝	技術部 JAN.13.10 胡彩娟

蘇州凱美電子有限公司  
SUZHOU KAIMEI ELECTRONIC LTD.  
江蘇省蘇州市相城區望亭鎮問渡路68號  
NO. 68 WENDU RD. WANGTING TOWNSHIP, XIANGCHENG DISTRICT, JIANGSU CHINA  
TEL: 0512-65383705  
FAX: 0512-65382688

SE410-28B

# JAMICON


(PE10AA4)

## ELECTROLYTIC CAPACITOR SPECIFICATION

CUSTOMER		ROPLA	
CODE	YOUR		NO. BFX1010015-1
	OUR	TLR102M1EG21RT9	DATE 2010/1/13
LOT NO.			POLARITY
CASE SIZE		10 × 21	SAFETY VENT
SERIES	TLR	TYPE	R
RATED VALUE		1000 uF	25 v

### DIMENSIONS (mm)

D	10 Φ	L'	≤L+1.5
D'	<D+0.5	F	5.0
d	0.6 Φ		



Item	Characteristics	
Operation temperature range	- 40 °C	~ + 105 °C
Capacitance Tolerance	- 20 %	~ + 20 %
Surge Voltage	32 VDC	
Leakage Current	I ≤ 250 (u A) after 2 minutes	
Dissipation Factor	≤ 14 (%)	120Hz 20 °C
Ripple Current	max 2250 (m A)	100kHz 105 °C
IMP.	< 0.022 (Ω)	100kHz 20 °C
Low Temperature Stability	Impedance Ratio At 120Hz	
	Z-25°C / Z+20°C	2 MAX
	Z-40°C / Z+20°C	3 MAX
Load Test	After 5000 Hrs At 105 °C	
	Capacitance Change	≤± 25 % of initial value
	D.F.(tan δ)	≤ 200 % of initial specified value
	Leakage Current	≤ initial specified value
	Out Look	Should be without any change
Terminal Strength	Pull Test	1.0 kg 10±1 sec
	Bend Test	0.5 kg 2 cycle
Soldering	245±3°C	Soldering must covered
	3±0.5sec	more than 95%
Storage Temperature	- 40 °C	~ + 105 °C

TEST FREQ.:120Hz	TEST TEMP:20°C	REFERENCE STANDARD: JIS C5101-4
------------------	----------------	---------------------------------

<b>SU ZHOU KAIMEI ELECTRONIC LTD.</b>	CHECKED	DESIGNED

SE410-28B