


High Voltage Switching Diode

LBAS21LT1G
FEATURE

- We declare that the material of product compliance with RoHS requirements.

DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LBAS21LT1G	JS	3000/Tape&Reel
LBAS21LT3G	JS	10000/Tape&Reel


MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Continuous Reverse Voltage	V_R	250	Vdc
Peak Forward Current	I_F	225	mAdc
Peak Forward Surge Current	$I_{FM(surge)}$	625	mAdc

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Total Device Dissipation FR- 5 Board, (1)	P_D	225	mW
$T_A = 25^\circ\text{C}$		1.8	mW/ $^\circ\text{C}$
Derate above 25°C			
Thermal Resistance, Junction to Ambient	R_{JJA}	556	$^\circ\text{C}/\text{W}$
Total Device Dissipation	P_D	300	mW
Alumina Substrate, (2) $T_A = 25^\circ\text{C}$		2.4	mW/ $^\circ\text{C}$
Derate above 25°C			
Thermal Resistance, Junction to Ambient	R_{JJA}	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (T A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Reverse Voltage Leakage Current ($V_R = 200\text{Vdc}$)	I_R	—	0.1	μAdc
($V_R = 200\text{Vdc}, T_J = 150^\circ\text{C}$)		—	100	
Reverse Breakdown Voltage ($I_{BR} = 100 \mu\text{Adc}$)	$V_{(BR)}$	250	—	Vdc
Forward Voltage ($I_F = 100 \text{mAdc}$)	V_F	—	1000	mV
($I_F = 200 \text{mAdc}$)		—	1250	
Diode Capacitance ($V_R = 0, f = 1.0 \text{ MHz}$)	C_D	—	5.0	pF
Reverse Recovery Time ($I_F = I_R = 30\text{mAdc}, R_L = 100 \Omega$)	t_{rr}	—	50	ns

 1. FR-5 = $1.0 \times 0.75 \times 0.062$ in.

 2. Alumina = $0.4 \times 0.3 \times 0.024$ in. 99.5% alumina.


LBAS21LT1G


Notes: 1. A 2.0 kΩ variable resistor adjusted for a Forward Current (I_F) of 30 mA.

2. Input pulse is adjusted so $I_{R(peak)}$ is equal to 30 mA.

3. $t_p \gg t_{rr}$

Figure 1. Recovery Time Equivalent Test Circuit

LBAS21LT1G
SOT-23

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

