
Mehrteilige Kabelschutzschläuche Split-Flex



Typ EWT-PAB split-flex







PRODUCT INFORMATION

The EWT-PAB cable protection conduits are made of specially modified polyamide 6. The material is halogen, phosphor and cadmium-free. Due to its excellent fire protection properties and very low smoke emission, this product can be used in railway technology and for static applications with medium to high mechanical stress.

igii illechanicai suess.

- The EWT-PAB cable protection conduits consist of a two-part, slotted conduit system and are characterised by the following advantages:
- The cable protection conduits can be opened and closed again at any time.
- Mounting of pre-assembled cables
- Retrofitting or repair in mechanical and plant engineering

SPECIFICATIONS



mod. polyamide PA 6



According to IEC EN 61386 Crush resistance: > 1300 N According to IEC EN 61386 Cycles: $> 1200 \sim$



-40 - 120 °C short term 160 °C



acc. to UL94 VO self-extinguishing











Туре	Order No.	Colour	A Ø mm	B Ø mm	R stat. mm	Weight kg/100m	MOQ m
Standard corrugation							
EWT-PAB M10/P07 Split-Flex, sw	83164650	Black	5.70	11.50	70.00	3.70	50
EWT-PAB M12/P09 Split-Flex, sw	83164652	Black	7.90	12.90	75.00	4.60	50
EWT-PAB M16/P11 Split-Flex, sw	83164654	Black	10.00	16.20	100.00	7.20	50
EWT-PAB M20/P16 Split-Flex, sw	83164656	Black	13.70	21.00	120.00	11.00	50
EWT-PAB M25/P21 Split-Flex, sw	83164658	Black	19.80	28.40	170.00	16.00	50
EWT-PAB M32/P29 Split-Flex, sw	83164660	Black	25.00	34.20	180.00	21.00	25
EWT-PAB M40/P36 Split-Flex, sw	83164662	Black	32.30	43.50	200.00	29.30	25
EWT-PAB M50/P48 Split-Flex, sw	83164664	Black	44.00	54.80	240.00	20.00	25

MATERIAL PROPERTIES



mod. polyamide PA 6



High angle consistency

Crush resistance: > 1300 N; Testing method: According to IEC EN 61386



Flexural fatigue strength

Cycles: $> 1200 \sim$; Testing method: According to IEC EN 61386

THERMAL PROPERTIES



Temperature / temperature range

-40 - 120 °C short term 160 °C

Mehrteilige Kabelschutzschläuche Split-Flex



Typ EWT-PAB split-flex

FIRE PROPERTIES



Fire classification

acc. to UL94 V0 self-extinguishing

Fire properties as per EN 45545-2

C.I.T. R22 / R23 HL3 = 0.61 Ds (max.) R22 / R23 HL3 = 68 L0I R22 / R23 HL3 = 32

TECHNICAL INFORMATION



Halogen-free

DIN 53474



UV-resistant acc. to ISO 4892-2

Wir empfehlen die Farbe Schwarz

CONFORMITY



RoHS (EC Directive 2011/65/EU)

APPROVALS AND OPERATING PERMITS



EU railway approval

EN 45545-2 R22/R23 3x HL3



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.