
Multi-sectional Split-Flex cable protection conduit



Type EWT-PP split-flex®







PRODUCT INFORMATION

The EWT-PP cable protection conduits are made of specially modified polypropylene. The material is phosphor and cadmium-free. For static applications involving light to medium mechanical loads.

The EWT-PP cable protection conduits consist of a two-piece slotted corrugated tube

system and feature the following advantages:

- Corrugated tubes can be opened and closed at any time.
- Mounting of pre-assembled cables
- Retrofitting or repair in mechanical and plant engineering

SPECIFICATIONS



Mod. Polypropylene



In conformity with IEC EN 61386 > 700 N



-40-130 °C transient / short term 150 °C



V2 self-extinguishing



1	
	Made in
ı	Germany
ų	

Туре	Order No.	Colour	A Ø mm	B Ø mm	R stat. mm	R dyn. mm	Weight kg/100m	Pack m
Standard corrugation								
EWT-PP M32/P29	83204260	Black	25.60	34.00	140.00	490.00	16.50	25

Suitable for

MATERIAL PROPERTIES



Mod. Polypropylene

MECHANICAL PROPERTIES



Crush resistance

Crush resistance: > 700 N; Testing method: In conformity with IEC EN 61386; Test value: M25/P21

THERMAL PROPERTIES



Temperature / temperature range

-40 - 130 °C transient / short term 150 °C

FIRE BEHAVIOUR



Fire classification

V2 self-extinguishing

CONFORMITY



RoHS (EC Directive 202/95/EC)

Multi-sectional Split-Flex cable protection conduit



Type EWT-PP split-flex®

GENERAL INFORMATION



Made in Germany

All details given in our sales material prospectuses and catalogues as well as the information available online are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.