

## m-seal ME (multi-insert)





## PRODUCT INFORMATION

The m-seal ME multi-insert is the perfect complement part to our m-seal cable fitting. The KV-ME multi-insert can be used to route several cables through one fitting. The fitted seal insert in the cable fitting is simply swapped for the ME multi-insert during assembly.

Please note that the cable diameter may be up to 20% less than the diameter of the hole, but must not undershoot the hole diameter

by less than 1 mm.

The m-seal ME multi-inserts feature the following advantages:

- Variable
- More cables through one fitting
- High protection class

NOT suitable for type WKK and type WKM cable fittings.

## **SPECIFICATIONS**



Elastomer



IP 65



-40 – 100 °C transient / short term



ode made not and ordinote and more did	motor oable mange					
Туре	Order No.	No. Openings	Diameter mm	Suitable for metric	Suitable for Pg	Pack qty.
m-seal ME M20/PG13,5-2x5	84182020	2	5.00	M20x1.5	Pg 13.5	50
m-seal ME M20/PG13,5-2x6	84182022	2	6.00	M20x1.5	Pg 13.5	50
m-seal ME M20/PG13,5-3x4	84182024	3	4.00	M20x1.5	Pg 13.5	50
m-seal ME M20/PG13,5-3x5	84182026	3	5.00	M20x1.5	Pg 13.5	50
m-seal ME M20/PG13,5-4x4	84182028	4	4.00	M20x1.5	Pg 13.5	50
m-seal ME M25-Blind	83980251			M25x1.5		50
m-seal ME M25-1x4	83980252	2		M25x1.5		50
m-seal ME M25-2x6	84182030	2	6.00	M25x1.5		50
m-seal ME M25-4x5	84182034	4	5.00	M25x1.5		50
m-seal ME M25-6x4	84182036	6	4.00	M25x1.5		50
m-seal ME M25-3x7	84182032	3	7.00	M25x1.5		50
m-seal ME M32-2x8	84182040	2	8.00	M32x1.5		50
m-seal ME M32-2x9	84182041	2	9.00	M32x1.5		50
m-seal ME M32-3x8	84182042	3	8.00	M32x1.5		50
m-seal ME M32-4x6	84182043	4	6.00	M32x1.5		50
m-seal ME M32-4x7	84182044	4	7.00	M32x1.5		50
m-seal ME M32-5x6	84182045	5	6.00	M32x1.5		50
m-seal ME M32-8x5	84182046	8	5.00	M32x1.5		50
m-seal ME M32-9x4	84182047	9	4.00	M32x1.5		50
m-seal ME M40-2x10	84182050	2	10.00	M40x1.5		50
m-seal ME M40-3x10	84182051	3	10.00	M40x1.5		50
m-seal ME M40-4x8	84182052	4	8.00	M40x1.5		50
m-seal ME M40-5x9	84182053	5	9.00	M40x1.5		50
m-seal ME M40-6x7	84182054	6	7.00	M40x1.5		50
m-seal ME M40-8x6	84182055	8	6.00	M40x1.5		50
m-seal ME M40-9x7	84182056	9	7.00	M40x1.5		50



# m-seal ME (multi-insert)

#### **MATERIAL PROPERTIES**



Elastomer



**Protection class** 

IP 65

## **THERMAL PROPERTIES**



**Temperature / temperature range** 

-40 - 100 °C transient / short term 120 °C



RoHS (EC Directive 202/95/EC)

All details given in our sales material prospectuses and catalogues as well as the information available online are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.