


# **Type SK shielding clamp**







#### PRODUCT INFORMATION

The shielding clamp may be used where the shield of individual cables must be connected with earth potential. The SK can be either screwed down on the mounting plate or snapped on to the 35 mm top-hat rail (EN 50022) by means of a mounting foot. SK mounting foot not included in delivery.

Please order separately.

## **SPECIFICATIONS**



Galvanised sheet steel



Туре	Order No.	Fastening	for sheath of Ø mm	A mm	B mm	C mm	Pack qty.
SK 4 – 13.5	87201062	M4x0,7	4.00 - 13.50	20.00	20.00	32.50	10

Suitable for

## **MATERIAL PROPERTIES**



Galvanised sheet steel

### **CONFORMITY**



RoHS (EC Directive 202/95/EC)

All details given in our sales material prospectuses and catalogues as well as the information available online are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.