

# ALUMINUM ELECTROLYTIC CAPACITORS

APPROVAL NO.


7760

NXQ 63 VB 220 (M)

SERIES	NXQ
RATING	63 V 220 $\mu$ F
CASE SIZE	$\varnothing$ 10 x 20 L

## A. DIAGRAM OF DIMENSION

[ UNIT : mm ]

B. MARKING: DARK BROWN SLEEVE & SILVER INK

FRONT VIEW OF CAPACITOR



BACK VIEW OF CAPACITOR

## C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE	:	-40 ~ +105 °C												
B. RATED VOLTAGE	:	63 V <sub>nc</sub>												
C. SURGE VOLTAGE	:	79 V <sub>nc</sub>												
D. CAPACITANCE TOLERANCE	:	±20% at 20°C, 120Hz												
E. LEAKAGE CURRENT	:	Lower 137 $\mu$ A, after 2 minutes at 20°C												
F. DISSIPATION FACTOR (TANδ)	:	Lower 0.09 at 20°C, 120Hz												
G. RATED RIPPLE CURRENT	:	1570 mA <sub>rms</sub> at 105°C, 100 kHz												
H. RATED RIPPLE CURRENT MULTIPLIERS (Frequency Multipliers)	:	<table border="1"> <tr> <td>Freq.(Hz)</td> <td>120</td> <td>1k</td> <td>10k</td> <td>50k</td> <td>100k</td> </tr> <tr> <td>Factor</td> <td>0.50</td> <td>0.73</td> <td>0.92</td> <td>0.95</td> <td>1.00</td> </tr> </table>	Freq.(Hz)	120	1k	10k	50k	100k	Factor	0.50	0.73	0.92	0.95	1.00
Freq.(Hz)	120	1k	10k	50k	100k									
Factor	0.50	0.73	0.92	0.95	1.00									
I. TEMPERATURE CHARACTERISTIC (Max. Impedance ratio)	:	<table border="1"> <tr> <td>Z(-25°C) / Z(20°C)</td> <td>2</td> </tr> <tr> <td>Z(-40°C) / Z(20°C)</td> <td>3</td> </tr> </table> <p style="text-align: right;">(at 120Hz)</p>	Z(-25°C) / Z(20°C)	2	Z(-40°C) / Z(20°C)	3								
Z(-25°C) / Z(20°C)	2													
Z(-40°C) / Z(20°C)	3													

J. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 10,000 hours at 105°C.

# Capacitance change ≤ ±25 % of the initial value

# Tanδ ≤ 200 % of the initial specified value

# Leakage Current ≤ The initial specified value

K. SHELF LIFE : The following specifications shall be satisfied when the capacitors are restored to 20°C, after exposing them for 500 hours at 105°C without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.

# Capacitance change ≤ ±25 % of the initial value

# Tanδ ≤ 200 % of the initial specified value

# Leakage Current ≤ The initial specified value

L. CLEANING CONDITIONS : Non-solvent proof

M. OTHERS : Satisfied characteristics KS C IEC 60384-4

※ IMP.(20°C, 100kHz) : 0.056 ( $\Omega$ ) ↓



Sam Young Electronics Co., Ltd.