ROPLA 2019.06.07

ALUMINUM ELECTROLYTIC CAPACITORS

APPROVAL NO.


10024


RFA 450 LG 4700 (M)

SERIES	RFA
RATING	450 V 4700 μF
CASE SIZE	Ø 76.5 × 145 L

A. DIAGRAM OF DIMENSION

[UNIT:mm]





ØD	76.5	
L	145	
F	31.5	

B. MARKING: <u>BLACK</u> SLEEVE & <u>GOLD</u> INK





450 V 4700 μF (M) 85°C

FRONT VIEW OF CAPACITOR

< SLEEVE or BOTTOM PLATE MARKING >

(1) (2) (3) (4)

- ① The ending figure of manufactured year in A.D
- ② Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,....Z,a,b,c,d,e)
- SAMYOUNG's symbol NO(1)

C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE : -25 ~ +85℃ : 450 V_{DC} **B. RATED VOLTAGE**

C. SURGE VOLTAGE : 500 Vpc

D. CAPACITANCE TOLERANCE : ± 20% at 20 ℃, 120Hz

E. LEAKAGE CURRENT F. DISSIPATION FACTOR (Tanδ)

: Lower <u>0.25</u> at 20℃, 120Hz **G. RATED RIPPLE CURRENT** 17.6 Arms at 85℃, 120Hz

H. TEMPERATURE CHARACTERISTICS

(CAPACITANCE CHANGE RATIO) $C(-25^{\circ}C)/C(20^{\circ}C) \ge 0.7 \text{ (at } 120^{\circ}Hz)$

I. INSULATION WITHSTANDING VOLTAGE

When a voltage of 2,000V_{AC} is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

J. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20℃

after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 20,000 hours at 85℃.

Capacitance change $: \le \pm 30 \%$ of the initial value

Tanδ : ≤ 300 % of the initial specified value

Leakage current : ≤ The initial specified value

K. SHELF LIFE: The following specifications shall be satisfied when the capacitors are restored to 20°C

after exposing them at 85°C for 500 hours without voltage applied.

The rated volage shall be applied to the capacitors for a minimum of 30 minutes,

at least 24 hours and not more than 48 hours before the measurements.

Capacitance change $: \le \underline{\pm 20 \%}$ of the initial value

Tanδ : ≤ 300 % of the initial specified value

Leakage current : ≤ The initial specified value

L. CLEANING CONDITIONS: Non-solvent proof

M. OTHERS : Satisfied charateristics KS C IEC 60384-4





