


ROPLA 2019.05.31


A. DIAGRAM OF DIMENSION







B. MARKING: <u>BLACK</u> SLEEVE & <u>GOLD</u> INK



FRONT VIEW OF CAPACITOR

< SLEEVE or BOTTOM PLATE MARKING >

- 1 2 3 4
- ① The ending figure of manufactured year in A.D
- ② Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,....Z,a,b,c,d,e)
- SAMYOUNG's symbol NO(1)

C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE : $\frac{-25}{}$ $\sim \frac{+85 \, ^{\circ}}{}$ B. RATED VOLTAGE : $\frac{450 \, \text{V}_{DC}}{}$ C. SURGE VOLTAGE : $\frac{500 \, \text{V}_{DC}}{}$

D. CAPACITANCE TOLERANCE : $\pm 20\%$ (at 20 °C, 120 Hz)

E. LEAKAGE CURRENT : Lower 5000 µA, after 5 minutes at 20 ℃

F. DISSIPATION FACTOR (Tan δ) : Lower <u>0.25</u> at 20 $^{\circ}$ C, 120 Hz G. MAX. RIPPLE CURRENT : <u>36.5 Arms</u> at 85 $^{\circ}$ C, 120 Hz

H. INSULATION WITHSTANDING VOLTAGE:

When a voltage of $2,000V_{AC}$ is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

I. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20 ℃ after the rated voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 5,000 hours at 85 ℃.

Capacitance change $\leq \pm 30 \%$ of the initial value

Tan δ \leq 300 % of the initial specified value

Leakage current ≤ The initial specified value

J. SHELF LIFE: The following specifications shall be satisfied when the capacitors are restored to 20 $^{\circ}$ C after exposing them at $85 ^{\circ}$ C for 500 hours without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes,

at least 24 hours and not more than 48 hours before measurements.

Capacitance change $\leq \pm 20 \%$ of the initial value

Tan δ \leq 300 % of the initial specified value

Leakage current ≤ The initial specified value

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied charateristics KS C IEC 60384-4

←	←	←

