**ROPLA** 2020.09.10

# **ALUMINUM ELECTROLYTIC CAPACITORS**

APPROVAL NO.


11307


**RGB 63 LG 47000** 

SERIES	RGB
RATING	63 V 47000 <i>μ</i> F
CASE SIZE	Ø 50 × 100 L

#### A. DIAGRAM OF DIMENSION

[UNIT:mm]





## **B. MARKING: BLACK SLEEVE & SLIVER INK**





RGB 63 V 47000 μF (M) 85°C

# FRONT VIEW OF CAPACITOR

## < SLEEVE or BOTTOM PLATE MARKING >

1 2 3 4

- 1) The ending figure of manufactured year in A.D.
- 2 Manufactured month(1,2,3....9,O,N,D)
- 3 Manufactured day (A,B,C,....Z,a,b,c,d,e)
- SAMYOUNG's symbol NO(1)

### C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE

**B. RATED VOLTAGE** C. SURGE VOLTAGE

D. CAPACITANCE TOLERANCE

±20% (at 20°C, 120Hz) **E. LEAKAGE CURRENT** 

Lower 5000 µA, after 5 minutes at 20 ℃ F. DISSIPATION FACTOR (Tan δ) Lower <u>0.45</u> at 20℃, 120Hz **G. RATED RIPPLE CURRENT** 13.2 Arms at 85℃, 120Hz

H. INSULATION WITHSTANDING VOLTAGE

When a voltage of 2,000V<sub>AC</sub> is applied for one minute between the terminals shorted each other and the mounting clamp on the insulating sleeve covering the case, there shall not be electrical damage.

<u>-40</u> ~ <u>+85℃</u>

63 V<sub>DC</sub>

79 V<sub>DC</sub>

I. LOAD LIFE: The following specifications shall be satisfied when the capacitors are restored to 20°C

after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) 2,000 hours at 85°C.

 $\leq$   $\pm 20 \%$  of the initial value # Capacitance change

# Tan δ ≤ 300 % of the initial specified value

# Leakage current ≤ The initial specified value

J. SHELF LIFE : The following specifications shall be satisfied when the capacitors are restored to 20  $^{\circ}$ 

after the exposing them at 85°C for 500 hours without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes,

at least 24 hours and not more than 48 hours before the measurements.

# Capacitance change  $\leq \pm 20 \%$  of the initial value

# Tan δ  $\leq$  300 % of the initial specified value

≤ The initial specified value # Leakage current

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied charateristics KS C IEC 60384-4

