

ALUMINUM ELECTROLYTIC CAPACITORS		APPROVAL NO. 10113																																																						
TLB 250 VS 1000 (M)	SERIES RATING CASE SIZE	TLB 250 V 1000 μF $\varnothing 35 \times 40 L$																																																						
A. DIAGRAM OF DIMENSION																																																								
<p>[UNIT : mm]</p>																																																								
B. MARKING: BROWN SLEEVE & SILVER INK																																																								
< VIEW OF CAPACITOR > <p>< FRONT > < BACK ></p>		< LOT No. : Sleeve or bottom plate marking. > ①②③④ or ①② ③④ ①②③④ ①②:YEAR : The ending of A.D. < DATE CODE : Sleeve marking. > ③④:WEEKS : 01 ~ 52																																																						
C. ELECTRICAL CHARACTERISTICS																																																								
<table> <tbody> <tr> <td>A. OPERATING TEMPERATURE RANGE</td> <td colspan="2">: <u>-25 ~ +105°C</u></td> </tr> <tr> <td>B. RATED VOLTAGE</td> <td colspan="2">: <u>250 V_{DC}</u></td> </tr> <tr> <td>C. SURGE VOLTAGE</td> <td colspan="2">: <u>300 V_{DC}</u></td> </tr> <tr> <td>D. CAPACITANCE TOLERANCE</td> <td colspan="2">: <u>$\pm 20\%$ at 20°C, 120Hz</u></td> </tr> <tr> <td>E. LEAKAGE CURRENT</td> <td colspan="2">: Lower <u>3000 μA</u>, after 5 minutes at 20°C</td> </tr> <tr> <td>F. DISSIPATION FACTOR (Tanδ)</td> <td colspan="2">: Lower <u>0.20</u> at 20°C, 120Hz</td> </tr> <tr> <td>G. RATED RIPPLE CURRENT</td> <td colspan="2">: <u>2.46 Arms</u> at 105°C, 120Hz</td> </tr> <tr> <td>H. TEMPERATURE CHARACTERISTIC (Max. Impedance ratio)</td> <td>Z(-25°C) / Z(20°C)</td> <td>4 (at 120Hz)</td> </tr> <tr> <td>I. LOAD LIFE</td> <td colspan="2">: The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for <u>7,000 hours</u> at <u>105°C</u>.</td> </tr> <tr> <td></td> <td># Capacitance change</td> <td>≤ <u>$\pm 25\%$ of the initial value</u></td> </tr> <tr> <td></td> <td># Tanδ</td> <td>≤ <u>300% of the initial specified value</u></td> </tr> <tr> <td></td> <td># Leakage current</td> <td>≤ <u>The initial specified value</u></td> </tr> <tr> <td>J. SHELF LIFE</td> <td colspan="2">: The following specifications shall be satisfied when the capacitors are restored to 20°C after the exposing them at <u>105°C</u> for <u>1,000 hours</u> without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.</td> </tr> <tr> <td></td> <td># Capacitance change</td> <td>≤ <u>$\pm 20\%$ of the initial value</u></td> </tr> <tr> <td></td> <td># Tanδ</td> <td>≤ <u>150% of the initial specified value</u></td> </tr> <tr> <td></td> <td># Leakage current</td> <td>≤ <u>The initial specified value</u></td> </tr> <tr> <td>K. CLEANING CONDITIONS</td> <td colspan="2">: Non-solvent proof</td> </tr> <tr> <td>L. OTHERS</td> <td colspan="2">: Satisfied characteristics KS C IEC 60384-4</td> </tr> </tbody> </table>			A. OPERATING TEMPERATURE RANGE	: <u>-25 ~ +105°C</u>		B. RATED VOLTAGE	: <u>250 V_{DC}</u>		C. SURGE VOLTAGE	: <u>300 V_{DC}</u>		D. CAPACITANCE TOLERANCE	: <u>$\pm 20\%$ at 20°C, 120Hz</u>		E. LEAKAGE CURRENT	: Lower <u>3000 μA</u> , after 5 minutes at 20°C		F. DISSIPATION FACTOR (Tanδ)	: Lower <u>0.20</u> at 20°C, 120Hz		G. RATED RIPPLE CURRENT	: <u>2.46 Arms</u> at 105°C, 120Hz		H. TEMPERATURE CHARACTERISTIC (Max. Impedance ratio)	Z(-25°C) / Z(20°C)	4 (at 120Hz)	I. LOAD LIFE	: The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for <u>7,000 hours</u> at <u>105°C</u> .			# Capacitance change	≤ <u>$\pm 25\%$ of the initial value</u>		# Tanδ	≤ <u>300% of the initial specified value</u>		# Leakage current	≤ <u>The initial specified value</u>	J. SHELF LIFE	: The following specifications shall be satisfied when the capacitors are restored to 20°C after the exposing them at <u>105°C</u> for <u>1,000 hours</u> without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.			# Capacitance change	≤ <u>$\pm 20\%$ of the initial value</u>		# Tanδ	≤ <u>150% of the initial specified value</u>		# Leakage current	≤ <u>The initial specified value</u>	K. CLEANING CONDITIONS	: Non-solvent proof		L. OTHERS	: Satisfied characteristics KS C IEC 60384-4	
A. OPERATING TEMPERATURE RANGE	: <u>-25 ~ +105°C</u>																																																							
B. RATED VOLTAGE	: <u>250 V_{DC}</u>																																																							
C. SURGE VOLTAGE	: <u>300 V_{DC}</u>																																																							
D. CAPACITANCE TOLERANCE	: <u>$\pm 20\%$ at 20°C, 120Hz</u>																																																							
E. LEAKAGE CURRENT	: Lower <u>3000 μA</u> , after 5 minutes at 20°C																																																							
F. DISSIPATION FACTOR (Tanδ)	: Lower <u>0.20</u> at 20°C, 120Hz																																																							
G. RATED RIPPLE CURRENT	: <u>2.46 Arms</u> at 105°C, 120Hz																																																							
H. TEMPERATURE CHARACTERISTIC (Max. Impedance ratio)	Z(-25°C) / Z(20°C)	4 (at 120Hz)																																																						
I. LOAD LIFE	: The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for <u>7,000 hours</u> at <u>105°C</u> .																																																							
	# Capacitance change	≤ <u>$\pm 25\%$ of the initial value</u>																																																						
	# Tanδ	≤ <u>300% of the initial specified value</u>																																																						
	# Leakage current	≤ <u>The initial specified value</u>																																																						
J. SHELF LIFE	: The following specifications shall be satisfied when the capacitors are restored to 20°C after the exposing them at <u>105°C</u> for <u>1,000 hours</u> without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.																																																							
	# Capacitance change	≤ <u>$\pm 20\%$ of the initial value</u>																																																						
	# Tanδ	≤ <u>150% of the initial specified value</u>																																																						
	# Leakage current	≤ <u>The initial specified value</u>																																																						
K. CLEANING CONDITIONS	: Non-solvent proof																																																							
L. OTHERS	: Satisfied characteristics KS C IEC 60384-4																																																							

