
2021.08.26 **ROPLA** APPROVAL NO. **ALUMINUM ELECTROLYTIC CAPACITORS** 12279 TLC **SERIES** TLC **VS 400** 330 (M) 400 V 330 μF **RATING** CASE SIZE Ø 25.4 \times 40 L A. DIAGRAM OF DIMENSION [UNIT : mm] PC board pin-out **Terminal** Sleeve **0.8** ^{+0.1} _{-0.2} **325.4+1max** 0.8.40.1 4.0±0.5 1.5 +0.2 2-ø2±0.1 4.0+0.5 Safety vent

B. MARKING: BROWN SLEEVE & SILVER INK

< VIEW OF CAPACITOR >



< FRONT >





< BACK >

< LOT No.: Sleeve or bottom plate marking. >

①:The ending figure of manufactured year in A.D. (1)(2)(3)(4)2:Manufactured month(1,2,3,...,9,O,N,D) or ③:Manufactured day (A,B,C,...,Z,a,b,c,d,e) (1)(2)

4:SAMYOUNG's (3)(4) Korea : 1, China : <1>

< DATE CODE : Sleeve marking. >

12:YEAR: The ending of A.D. (1)(2)(3)(4)③ 4:WEEKS: 01~52

C. ELECTRICAL CHARACTERISTICS

A. OPERATING TEMPERATURE RANGE : <u>- 25</u> ~ <u>+105℃</u>

: 400 V_{DC} **B. RATED VOLTAGE** C. SURGE VOLTAGE : 450 V_{DC}

D. CAPACITANCE TOLERANCE : ± 20% at 20℃, 120Hz

E. LEAKAGE CURRENT : Lower 2640 µA, after 5 minutes at 20 ℃

F. DISSIPATION FACTOR (Tanδ) : Lower 0.15 at 20 ℃, 120Hz **G. RATED RIPPLE CURRENT** : 1.33 Arms at 105 ℃, 120Hz

H. TEMPERATURE CHARACTERISTIC

Z(-25°C) / Z(20°C) (Max. Impedance ratio) (at 120Hz)

I. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage with the rated ripple current is applied (the peak voltage shall not

exceed the rated voltage) for 5,000 hours at 105 °C.

Capacitance change ≤ ±25 % of the initial value

Tanδ ≤ 250 % of the initial specified value

Leakage current ≤ The initial specified value

J. SHELF LIFE: The following specifications shall be satisfied when the capacitors are restored to 20°C

after exposing them at 105°C for 1,000 hours without voltage applied.

The rated voltage shall be applied to the capacitors for a minimum of 30 minutes,

at least 24 hours and not more than 48 hours before the measurements.

Capacitance change ≤ ±20 % of the initial value

Tanδ ≤ 150 % of the initial specified value

Leakage current ≤ The initial specified value

K. CLEANING CONDITIONS: Non-solvent proof

L. OTHERS : Satisfied characteristics KS C IEC 60384-4

