
## EDLC 2.5V 25F

## **FEATURES**

Electric double layer capacitor Higher power density with ultra low ESR Semi-permanent, quick charge and discharge than batteries Suitable for short-term peak power assistance application UL and ISO/TS certificated, RoHS compliant Radial design with lead terminal type

## DIMENSIONS



Dimensions in mm						
D +1.0 Max	L ± 1.5	d ± 0.1	P ± 0.5			
Ф16.0	25.0	Φ0.8	7.5			

This drawing is not to be scaled.

## **SPECIFICATIONS**

Part Number	Rated Voltage, V <sub>R</sub>	Rated Capacitance	AC ESR 1kHz	DC IR	Maximum Current	Leakage Current	Stored Energy	Dimension D x L	Weight
	(V)	(F)	(mΩ)	(mΩ)	(A)	(mA)	(J)	(mm)	(g)
VEC 2R5 256 QG	2.5	25.	40.00	60.00	13.	0.050	78.1	16.0 x 25.0	7.9
* Maximum Current: 1 second discharge to ½·V <sub>R</sub>									

\* Leakage Current: After 72hours at  $V_R$  and 25 °C

ltem	Characteristics	Remarks
Rated Voltage(V <sub>R</sub> )	2.5V	
Capacitance Tolerance	-10 ~ 30%	
		$ \Delta cap  \le 30\%$ of initial value at 25 $^{\circ}C$
Operating Temperature (T <sub>min</sub> ~ T <sub>max</sub> )	<b>-25 ~ +70</b> ℃	$ \Delta ESR  \le 100\%$ of specified value at 25 $^\circ C$
( Thin Thay		After 1,000 hours application of $V_R$ at $T_{max}$
Storage Temperature	<b>-40 ~ 70</b> ℃	
	500,000 cycles	$ \Delta cap  \le 30\%$ of initial value at 25 $^{\circ}C$
Cycle Life		$ \Delta ESR  \le 100\%$ of specified value at 25 $^\circ C$
		Cycles from V <sub>R</sub> to $\frac{1}{2}$ ·V <sub>R</sub> under constant current at 25°C
		Δcap  ≤ 10% of initial value at 25 ℃
Shelf Life	2 years	$ \Delta ESR  ≤ 50\%$ of specified value at 25 °C
		Without electrical charge under T <sub>max</sub>



Tel: +82-31-455-3064 E-mail: hycap@vina.co.kr Web: www.vina.co.kr Design and specifications are subjected to change without notice. version 9.1 on November 23, 2015





Ð