
## EDLC 2.5V 360F

## **FEATURES**

Electric double layer capacitor Higher power density with ultra low ESR Semi-permanent, quick charge and discharge than batteries Suitable for short-term peak power assistance application UL and ISO/TS certificated, RoHS compliant Radial design with 4-pin snap-in terminal type

## DIMENSIONS



Dimensions in mm						
D +1.5 Max	+1.5 Max L ± 2.0		P ± 0.2			
Ф35.0	62.0	6.0	10.0			

This drawing is not to be scaled.

## SPECIFICATIONS

Part Number	Rated Voltage, V <sub>R</sub>	Rated Capacitance	AC ESR 1kHz	DC IR	Maximum Current	Leakage Current	Stored Energy	Dimension D x L	Weight
	(V)	(F)	(mΩ)	(mΩ)	(A)	(mA)	(J)	(mm)	(g)
VEC 2R5 367 QG	2.5	360.	6.00	10.00	97.	0.720	1,125.0	35.0 x 62.0	71.0
* Maximum Current: 1 second discharge to ½·V <sub>R</sub>									

\* Leakage Current: After 72hours at  $V_R$  and 25 °C

Item	Characteristics	Remarks
Rated Voltage(V <sub>R</sub> )	2.5V	
Capacitance Tolerance	-10 ~ 30%	
Operating Temperature (T <sub>min</sub> ~ T <sub>max</sub> )		$ \Delta cap  \le 30\%$ of initial value at 25 °C
	<b>-25 ~ +70</b> ℃	$ \Delta ESR  \le 100\%$ of specified value at 25 $^{\circ}$ C
(•min •max/		After 1,000 hours application of $V_R$ at $T_{max}$
Storage Temperature	-40 ~ 70 ℃	
		∆cap  ≤ 30% of initial value at 25 ଁC
Cycle Life	500,000 cycles	$ \Delta ESR  \le 100\%$ of specified value at 25 $^{\circ}$ C
		Cycles from $V_R$ to $1/2 \cdot V_R$ under constant current at 25°C
	2 years	∆cap  ≤ 10% of initial value at 25 ℃
Shelf Life		$ \Delta ESR  \le 50\%$ of specified value at 25 $^{\circ}$ C
		Without electrical charge under T <sub>max</sub>



Tel: +82-31-455-3064 E-mail: hycap@vina.co.kr Web: www.vina.co.kr Design and specifications are subjected to change without notice. version 9.1 on November 23, 2015



