
EDLC 2.5V 5F

FEATURES

Electric double layer capacitor Higher power density with ultra low ESR Semi-permanent, quick charge and discharge than batteries Suitable for short-term peak power assistance application UL and ISO/TS certificated, RoHS compliant Radial design with lead terminal type-p8

DIMENSIONS



Dimensions in mm						
D +1.0 Max	L ± 1.5	Z ± 0.1	P ± 0.5			
Ф8.0	25.0	0.6	3.5			

This drawing is not to be scaled.

SPECIFICATIONS

Part Number	Rated Voltage, V _R	Rated Capacitance	AC ESR 1kHz	DC IR	Maximum Current	Leakage Current	Stored Energy	Dimension D x L	Weight
	(V)	(F)	(mΩ)	(mΩ)	(A)	(mA)	(J)	(mm)	(g)
VEC 2R5 505 QA	2.5	5.	120.00	200.00	3.	0.010	15.6	8.0 x 25.0	1.9
* Maximum Current: 1 second discharge to ½·V _R									

* Leakage Current: After 72hours at V_R and 25 °C

ltem	Characteristics	Remarks
Rated Voltage(V _R)	2.5V	
Capacitance Tolerance	-10 ~ 30%	
		$ \Delta cap ≤ 30\%$ of initial value at 25 °C
Operating Temperature (T _{min} ~ T _{max})	-25 ~ +70 ℃	$ \Delta ESR \le 100\%$ of specified value at 25 $^{\circ}$ C
(•min •max)		After 1,000 hours application of V_R at T_{max}
Storage Temperature	-40 ~ 70 ℃	
		$ \Delta cap ≤ 30\%$ of initial value at 25 °C
Cycle Life	500,000 cycles	$ \Delta ESR $ ≤ 100% of specified value at 25 °C
		Cycles from V_R to $\frac{1}{2} \cdot V_R$ under constant current at 25°C
		∆cap ≤ 10% of initial value at 25 ℃
Shelf Life	2 years	$ \Delta ESR \le 50\%$ of specified value at 25 $^{\circ}$ C
		Without electrical charge under T _{max}



Tel: +82-31-455-3064 E-mail: hycap@vina.co.kr Web: www.vina.co.kr Design and specifications are subjected to change without notice. version 9.1 on November 23, 2015





Æ