
2-Serial Module 5.4V 2.5F




FEATURES

Electric double layer capacitor
2 cells serially connected supercapacitor
Semi-permanent, quick charge and discharge than batteries
Suitable for smart meter or car driving recorder application
UL and ISO/TS certificated, RoHS compliant
Radial design with lead terminal type customized in 3 ways



DIMENSIONS



Dimensions in mm						
D +0.1 Max	W ± 1.0	L ± 1.5	d ± 0.1		P ± 0.2	
Ф8.5	17.0	27.0	Ф0.6	l: 4.7	O: 12.3	H: 8.5

This drawing is not to be scaled.

SPECIFICATIONS

Part Number	Rated Voltage, V _R	Rated Capacitance	AC ESR 1kHz	DC IR	Maximum Current	Leakage Current	Stored Energy	Dimension D x W x L	Weight
	(V)	(F)	$(m\Omega)$	$(m\Omega)$	(A)	(mA)	(J)	(mm)	(g)
VEC 5R4 255 QA-X	5.4	2.5	75.00	125.00	5.	0.010	36.5	8.5 x 17.0 x 27.0	4.5

^{*} X is variant type code such as I, O or H.

Item	Characteristics	Remarks
Rated Voltage(V _R)	5.4V	
Capacitance Tolerance	-10 ~ +30%	
.		∆cap ≤ 30% of initial value at 25 ℃
Operating Temperature $(T_{min} \sim T_{max})$	-40 ~ +65 ℃	ΔESR ≤ 100% of specified value at 25 ℃
('min 'max/		After 1,000 hours application of V_R at T_{max}
Storage Temperature	-40 ~ 70 ℃	
		∆cap ≤ 30% of initial value at 25 ℃
Cycle Life	500,000 cycles	ΔESR ≤ 100% of specified value at 25 ℃
		Cycles from V_R to $1/2 \cdot V_R$ under constant current at 25°C
	2 years	Δcap ≤ 10% of initial value at 25 ℃
Shelf Life		$ \Delta ESR $ ≤ 50% of specified value at 25 $^{\circ}$ C
		Without electrical charge under T _{max}



Tel: +82-31-455-3064 E-mail: hycap@vina.co.kr Web: www.vina.co.kr Design and specifications are subjected to change without notice. version 9.1 on November 23, 2015

^{*} Maximum Current: 1 second discharge to ½·V_R