2-Serial Module 6.0V 5F




FEATURES

Electric double layer capacitor
2 cells serially connected supercapacitor
Semi-permanent, quick charge and discharge than batteries
Suitable for smart meter or car driving recorder application
UL and ISO/TS certificated, RoHS compliant
Radial design with lead terminal type customized in 3 ways



DIMENSIONS



Dimensions in mm						
D +0.1 Max	W ± 1.0	L ± 1.5	d ± 0.1		P ± 0.2	
Ф10.5	21.0	32.0	Ф0.6	l: 5.5	O: 15.5 H: 10.5	

This drawing is not to be scaled.

SPECIFICATIONS

Part Number	Rated Voltage, V _R	Rated Capacitance	AC ESR 1kHz	DC IR	Maximum Current	Leakage Current	Stored Energy	Dimension D x W x L	Weight
	(V)	(F)	$(m\Omega)$	$(m\Omega)$	(A)	(mA)	(J)	(mm)	(g)
VEC 6R0 505 QG-X	6.0	5.	55.00	85.00	10.	0.030	90.0	10.5 x 21.0 x 32.0	6.6

^{*} X is variant type code such as I, O or H.

Item	Characteristics	Remarks
Rated Voltage(V _R)	6.0V	
Capacitance Tolerance	-10 ~ +30%	
O " T		Δcap ≤ 30% of initial value at 25 °C
Operating Temperature (T _{min} ~ T _{max})	-40 ~ +65℃	ΔESR ≤ 100% of specified value at 25 ℃
(· IIIIII · IIIax)		After 1,000 hours application of V_R at T_{max}
Storage Temperature	-40 ~ 70 ℃	
		Δcap ≤ 30% of initial value at 25 °C
Cycle Life	500,000 cycles	ΔESR ≤ 100% of specified value at 25 ℃
		Cycles from V_R to $1/2 \cdot V_R$ under constant current at 25°C
		Δcap ≤ 10% of initial value at 25 ℃
Shelf Life	2 years	ΔESR ≤ 50% of specified value at 25 °C
		Without electrical charge under T _{max}



Tel: +82-31-455-3064 E-mail: hycap@vina.co.kr Web: www.vina.co.kr Design and specifications are subjected to change without notice. version 9.1 on November 23, 2015

^{*} Maximum Current: 1 second discharge to ½·V_R